

# CONSTANTEMP HEATER



## FEATURES

---

- Single or Double Wall Exchanger
- Accuracy  $\pm 2^{\circ}\text{F}$
- Feed-Forward Control
- Flows up to 120 GPM
- Adjustable Temperature 105-180°F
- No Storage Tank Required
- Built In Safety
- Heats Water Only on Demand
- Fits Through Standard Doorways
- High Turndown

## OPTIONS

---

- Skidded
- Recirculation Kit
- Automatic Descaler
- Insulated Cover
- Pressure Gradient Monitor

## MODELS

---

- L - Single Wall
- LDW- Double Wall

## APPLICATION DATA

---

- Hospital Patient & Domestic Hot Water
- University Dormitories
- Safety Shower Systems
- Industrial Shower Rooms
- Booster Heater
- Building Heat

## RATINGS

---

### Adjustable temperature range:

45-120 GPM: 105-180°F (41-82°C)

15 and 30 GPM: 105-150°F (41-65°C)

**Steam pressure:** 2-250 PSIG (14-1725 kPa)  
over 15 (104 kPa), requires steam reducing valve

**Water pressure:** 150 PSI max. (1034 kPa)  
Option: 250 PSI max. (1723 kPa)(single wall only)

### Flow ranges:

Single Wall: 15, 30, 45, 60, 75, 90, 105, 120 GPM  
(57, 114, 170, 227, 284, 341, 397, 454 L/min)

Double Wall: 30, 60, 90, 120 GPM (114, 227, 341,  
454 L/min)

SIZING INFORMATION  
GENERAL PAGE 22  
CONSTANTEMP PAGE 26

This document was created with Win2PDF available at <http://www.win2pdf.com>.  
The unregistered version of Win2PDF is for evaluation or non-commercial use only.  
This page will not be added after purchasing Win2PDF.