

## Float & Thermostatic Steam Trap Capacities

### FT SERIES TRAPS

Capacities in lb/h hot condensate

Model	Size	Orifice Inches/mm	Differential Pressure, psi				
			1/4	1/2	1	2	5
FT14-4.5	1/2", 3/4"	.157/4	115	155	205	265	390
FT14-10	1/2", 3/4"	.110/2.8	56	76	100	137	200
FT14-14	1/2", 3/4"	.079/2	40	53	71	95	138
FT14-4.5	1"	.276/7	374	529	748	1058	1566
FT14-10	1"	.205/5.2	163	230	325	459	695
FT14-14	1"	.157/4	109	154	218	309	441
FT14-4.5	1-1/2"	.689/17.5*	975	1378	1949	2756	4388
FT14-10	1-1/2"	.591/15*	608	860	1216	1720	2700
FT14-14	1-1/2"	.531/13.5*	394	557	788	1114	1764
FT14-4.5	2"	1.122/28.5*	3196	4520	6392	9040	14332
FT14-10	2"	.807/20.5*	1637	2315	3274	4630	7166
FT14-14	2"	.657/16.7*	780	1102	1559	2205	3418
FT450-4.5	3/4"	.157/4	110	155	219	310	440
FT450-10	3/4"	.126/3.2	65	91	129	183	275
FT450-14	3/4"	.106/2.7	47	66	93	132	203
FT20-21 FT450-21	1/2" 3/4"	.079/2.0	25	35	50	70	110
FT450-32	3/4"	.063/1.6	16	22	31	44	66
FT10-65	1"	.276/7	770	950	1100	1250	1655
FT450-10	1"	.205/5.2	202	285	403	570	870
FT450-14	1"	.185/4.7	150	212	300	425	640
FT450-21	1"	.157/4	110	155	219	310	440
FT450-32	1"	.126/3.2	65	91	129	183	275
FT10-65	1-1/2"	.689/17.5*	1100	1750	2418	3420	5733
FT450-10	1-1/2"	.591/15*	624	882	1247	1764	2734
FT450-14/21/32	1-1/2"	.531/13.5*	407	575	813	1150	1764
FT10-65	2"	1.122/28.5*	10020	12200	13400	15600	18522
FT450-10	2"	.807/20.5*	1559	2205	3118	4410	6950
FT450-14/21/32	2"	.657/16.7*	780	1103	1559	2705	3528

\*each orifice of double seated trap

**NOTE: for FT32 and FT46, use capacities for FT450.**

This document was created with Win2PDF available at <http://www.win2pdf.com>.  
The unregistered version of Win2PDF is for evaluation or non-commercial use only.  
This page will not be added after purchasing Win2PDF.